

A WORLD LEADER IN FUME **EXTRACTION TECHNOLOGY**



MECHANICAL ENGINEERING





Industrial particle and dust extractor.

This unit has been developed for the safe and effective removal of swarf and smaller particulates during processes such as routing, mechanical engraving, grinding and turning. Its brushless motor is designed for continuous running and generates high vacuums while being quiet in operation. The large capacity bag filter has a very high

Technology



HEPA filter



ProTECT service plan



SureCHECK quality standard

Key features of the DustPRO 100

Filters with long life and low replacement cost Standard

HEPA filter Standard

Filter change / system fail signal Optional

Audible alarm for filter condition Standard

Remote stop / start interface Optional

Contact BOFA at https://bofainternational.com/en/contact/

https://bofainternational.com/en/portal/datasheets/dustpro-100/
















Technical specification



Airflow through filters



Bag filter




Clean air



Contaminated air



HEPA filter



Technical data		
	EU	
Dimensions (HxWxD)	570 x 460 x 730mm / 22.44 x 18.11 x 28.74"	
Cabinet construction	Powder coated mild steel	
Airflow / Pressure	180m³/hr / 110mbar / 105cfm	
Electrical data	230V 1ph 50/60Hz	
	Full load current: 7 amps / 0.8kw	
	3m hard wired power cable	
	Illuminated 10A trip ON / OFF switch	
Noise level	< 65dBA at typical operating speed	
Weight	58kgs (127.6 lbs)	
Approvals	CE	

Bag filter specifications	
Filter holding capacity	20 Ltrs

Bag filter specifications		
Filter media	Polyester	
Filter media construction	Bag filter	
Filter efficiency	95% @ 0.9 microns	

HEPA filter specifications	
HEPA filter media	Glass fibre
HEPA media construction	Maxi pleat construction with webbing spacers
Filter efficiency	99.997% @ 0.3 microns

Part numbers			
Model	Voltage	Part no.	24V stop / start
DustPRO 100 Powder coated	230V	D0542A	A2001

Replacement filters			
Model	Bag filter part no.	HEPA filter part no.	
DustPRO 100	A1030134	A1030161	

Datasheet correct at time of publishing.

Where applicable, the carbon used in BOFA units is capable of removing a wide range of VOC's, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Think before you print! Please consider the environment before printing this document.



Mail: infoMJB@mjb.fr - www.mjb.fr